

DANGER

HIGH VOLTAGE

**AIR HORN
SIGNALS**

**-EMERGENCY-1ST AID-
3 SHORT BLASTS**

**EVACUATION
2 30 SEC. BLASTS**

SITE SAFETY RULES

- ① SUBSTANTIAL FOOTWEAR WITH SAFETY TOES SHALL BE WORN.
- ② HARD HATS MUST BE WORN WHILE ON SITE.
- ③ HAND, EYE AND SKIN PROTECTION IS REQUIRED WHEN EXPOSED TO INJURY HAZARDS.
- ④ NO HORSE PLAY OF ANY KIND WITH BE TOLERATED.
- ⑤ GUARDRAILS AND HANDRAILS ARE NOT TO BE REMOVED UNLESS SO REQUIRED BY THE WORK IN THE IMMEDIATE AREA. RAILINGS SO REMOVED MUST BE REPLACED BEFORE WORKER LEAVES THE AREA.
- ⑥ SCAFFOLDING PLANKS AND BEAMS MUST BE OF SOUND MATERIAL CLEAR OF DEFECTS. DO NOT USE POORLY CONSTRUCTED SCAFFOLDING. SEE THAT SCAFFOLDING IS PROVIDED WITH GUARDRAILS.
- ⑦ LADDERS MUST BE SECURE TOP AND BOTTOM. DO NOT USE POORLY CONSTRUCTED OR DEFECTIVE LADDERS.
- ⑧ WASTE SHALL NOT BE ALLOWED TO ACCUMULATE. REGULAR DAILY CLEANUP IS REQUIRED.
- ⑨ NO MUSIC ALLOWED ON SITE.
- ⑩ ANY WORKER, AS DETERMINED BY SITE SUPERINTENDENT FOUND TO BE UNFIT FOR HIS OR HER DUTIES WILL BE REMOVED FROM SITE.
- ⑪ PERSONS FAILING TO COMPLY WITH THE ABOVE OR ANY W.C.B. REGULATIONS AND THEREBY CAUSING HAZARDS EITHER TO HIMSELF OR HIS FELLOW WORKERS WILL BE REMOVED FROM SITE.

**THINK SAFETY!
THANK YOU FOR YOUR CO-OPERATION**

CAUTION

**ASBESTOS Under
Roof Tile**

Consult OSH Standard 306 or your safety office before removing or working on this material. Safety precautions are required.